# logitech®

# **Rally Bar Mini**



Rally Bar Mini is Logitech's most advanced and versatile all-in-one video bar for small rooms. With studio-quality audio and video, motorised pan and tilt, and Al-driven performance, Rally Bar Mini sets a new standard for team collaboration. Connect to a computer or run in appliance mode with supported video conferencing services.

### WHAT'S IN THE BOX

Rally Bar Mini Power supply AC power cord HDMI cable USB cable Remote control Lens caps for main lens and AI Viewfinder User documentation

# FEATURES

System Requirements Internet Connection: Wired or wireless USB Mode: Windows® 10 or later, Windows® 7 with the latest service pack, latest 2 versions of macOS Appliance Mode: Room solution software license (not included)

# logitech

## PACKAGE SPECIFICATIONS

	Primary pack	Master shipper carton
Part #	991-000390	N/A
Bar code	5099206102163 (EAN-13)	50992061021610 (SCC-14)
Weight gr	8869	8870
Length cm	80.2	80.8
Width cm	25.2	25.8
Height/depth cm	28.9	30.2
Volume	58.41 dm3	0.06m3
1 primary pack	1	N/A
1 master shipper carton	1	1
1 pallet EURO	15	15
1 container 20 ft	406	406
1 container 40 ft	840	840
1 container 40 ft HQ	960	960

#### SYSTEM REQUIREMENTS

#### General

Built-in Components: 6 beamforming microphones, PTZ camera, 3 speakers, Al Viewfinder, cable management & retention system, table stand, Logitech CollabOS platform Enclosure: All-in-one enclosure with integrated table stand and patented

and audio interference Device Management: Logitech Sync

Displays Supported: 2 Display Resolution: Up to 4k

#### Dimensions:

Height: 128 mm (5.04 in) Width: 719 mm (2.31 in) Depth: 120 mm (4.72 in) Weight: 4.03 kg (8.88 lbs)

#### Camera

Resolution: 4K, 1440p, 1080p, 900p, 720p, and SD at 30fps Pan: Motorized ±25° Tilt: Motorized ±15° Zoom: 4X HD digital zoom Diagonal Field of View: 120° Horizontal Field of View: 113° Vertical Field of View: 80.7° Total Room Coverage (field of view + pan and tilt): 163° horizontal x 110° vertical

#### Speakers

Woofer: 70mm /2.7in Mid-range: 2x /1.5in Output: 90dB SPL @1W, 99dB SPL @8.0W, both +/-2dB at ½ meter Sensitivity: 86+/-2dB SPL at 1W, ½ meter THD: 1kHz < 2% Speaker Sampling Rate: 48 kHz

#### Microphones

Frequency Response: 90Hz • 16kHz Sensitivity: >-36dBFS +/-1dB @ 1Pa Microphone Data Rate Output: 48 kHz Pickup Range: 4.5 m /15 ft Beamforming Elements: Six omnidirectional digital MEMS microphones forming five adaptive acoustic broadside beams Audio Processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector) Noise Suppression: Al filter Add-on Mics: Supports up to 2 additional Rally Mic Pods

### **TECHNICAL SPECS**

RightSense™ Technologies RightLight™: Renders natural skin tones for each participant. RightSight™: Maintains persistent room awareness and detects human figures to auto-frame participants. RightSound™: Distinguishes speech from other sounds to auto-level voices while suppressing background noise and echo.

Interfaces HDMI Out: 2 HDMI In: 1 USB 3.0: 3x Type A, 1x Type C Network: 10/100/1G Ethernet WiFi: 802.11a/b/g/n/ac (MIMO) External Mic Input: Yes (proprietary input supports optional Rally Mic Pod, Rally Mic Pod Hub, and Rally Mic Pod Extension Cable) Remote Control: Bluetooth® Low Energy

#### Power & Cables

Power Supply: Auto-sensing Operating Voltage/Power: 100-240V, 19V, 4.74A Power Supply Dimensions: 127mm x 51mm x 30mm DC Cable: 1.5 m /4.9 ft AC Cable: 1 m /3.28 ft HDMI 1.4 Cable: 2 m /6.5 ft USB A to USB C 3.0 Cable: 2.2 m /7.2 ft

#### Environmental Operating Temperature: 0 to 40 °C Storage Temperature: -40 to 70 °C Humidity: 10 to 95% BTU/hr: 57 idle, 64 in meeting

Security Full Disk Encryption: AES-128 Data Encryption: Symmetric Keys, PKI Device Identity: Protected by device attestation Device Access: Authenticated using API Key Protection: Arm TrustZone, RPMP

#### Guarantee

Standard: 2 years limited hardware guarantee included Extended: Additional one year extended guarantee available at the time of hardware purchase. Contact your reseller for availability.

Accessories Mounts: Wall Mount for Video Bars, TV Mount for Video Bars Audio: Rally Mic Pod, Rally Mic Pod Hub, Rally Mic Pod Mount, Rally Mic Pod Extension Cable Connectivity: Logitech Strong USB (10m, 25m, 45m) Touch Controller: Logitech Tap