logitech®

RoomMate + Tap IP



Make video collaboration easier for employees and IT admins by adding Logitech Tap IP touch controller and Logitech RoomMate appliance to any meeting space with an existing Logitech conference camera. Configure the room for leading video conferencing platforms, including Zoom Rooms, RingCentral, and others.

WHAT'S IN THE BOX

FEATURES

System Requirements
Internet Connection: Wired or wireless
Appliance Mode: Room solution software license (varies by service provider, not included)



PACKAGE SPECIFICATIONS

	Primary pack	Master shipper carton
Part #	991-000400	N/A
Bar code	5099206102101 (EAN-13)	50992061021016 (SCC-14)
Weight gr	4999	5000
Length cm	37.3	38
Width cm	25.2	25.9
Height/depth cm	18.9	20.3
Volume	17.77 dm3	0.02m3
1 primary pack	1	N/A
1 master shipper carton	1	1
1 pallet EURO	72	72
1 container 20 ft	1463	1463
1 container 40 ft	3014	3014
1 container 40 ft HQ	3640	3640

SYSTEM REQUIREMENTS

Kit Components Logitech Tap IP Logitech RoomMate Logitech Compute Mount

Logitech Tap IP

Network-connected touch controller for starting and joining video meetings

Touch Screen: 257 mm (10.1 in) diagonal screen with 14° display angle Resolution: 1280 x 800

Cabling: Power over Ethernet (PoE) (cable not included), IEEE 802.3af Type 1, Class 3 device

Cable Management: Internal cable retention and strain relief system

Ethernet: 10/100mbps Wi-Fi: 802.11a/b/g/n/ac

Device Management: Logitech Sync

Color: Graphite

Mounting: 100 mm x 100 mm VESA FDMI

Dimensions (H x W x D): 58 mm (2.3 in) x 244 mm (9.6 in) x 179 mm (7.0

TECHNICAL SPECS

Logitech RoomMate

CollabOS appliance purpose-built for video conferencing

Compatibility: Supports Zoom Rooms Appliances, RingCentral Rooms, and other video conferencing platforms

Appliance Mode: Zoom Rooms, RingCentral Rooms. For the latest information on certifications and compatibility, visit www.logitech.com/ support/vc-certifications.

Operating System: Logitech CollabOS 1.4 or higher

Device Management: Logitech Sync and supported device management

Certified Hardware: Logitech MeetUp, Rally Camera, Rally System, Rally Plus System, Tap, Tap IP

Verified Hardware: Biamp TesiraFORTÉ X 400, QSC Q-SYS Core 8 Flex, Shure IntelliMix P300. For latest information on compatible products, contact your preferred partner.

Network Protocol Support: IPv4, IPv6

Proxy Support: IP based Proxy, FQDN based Proxy, Proxy using PAC file

Interfaces HDMI Out: 2 HDMI In: 1 USB: 3x Type A

Network: 10/100/1G Ethernet WiFi: 802.11a/b/g/n/ac

Operating Voltage/Power: 100-240V, 19V, 4.74A

Full Disk Encryption: AES-128

Data Encryption: Symmetric Keys, PKI

Device Identity: Protected by device attestation Device Access: Authenticated using API Key Protection: Arm TrustZone, RPMP Device Security: Kensington Lock

Color: White

Dimensions: (H x W x D): 34.5 mm (1.36 in) x 161 mm (6.34 in) x 211 mm

(8.31 in)

Logitech Compute Mount

Clean and secure mounting option for Logitech RoomMate and other compute devices with 100x100 or 75x75 VESA pattern

Dimensions: (H x W x D): 35 mm (1.38 in) x 164 mm (6.46 in) x 350 mm (13.78 in)

Warranty

Standard: 2-year limited hardware warranty included

Extended: 1-year and 3-year extended warranties available at the time of

hardware purchase. Contact your reseller for availability.

Accessories

Logitech Tap IP: Table Mount, Riser Mount, Wall Mount