

TUF GAMING VG34VQ3B MONITOR



KEY FEATURES

180Hz
Rapid Refresh
Rate

High refresh rate for ultra fast and smooth gameplay

1ms

1ms MPRT response time for sharp gaming visuals with high frame rates



Enables ELMB together with VRR, eliminating ghosting and tearing for sharp gaming visuals



DisplayWidget Center

Lets users easily change monitor settings via an intuitive interface

**Variable
Overdrive**

Allows the display to dynamically alter its overdrive setting



Shadow Boost

To enhance the details in dark scenes



Support wide color gamut to reproduce vivid color




Curved Design

1500R curvature design for immersive gameplay



With Low Input Lag, you can hit that target just in time



TUF Gaming VG34VQ3B has undergone stringent performance tests and is certified Flicker-free and Low Blue Light (Software solution) by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services.



TUF GAMING VG34VQ3B MONITOR

Display	Panel Size (inch) : 34	
	Aspect Ratio : 21:9	
Video Feature	Display Viewing Area (H x V) : 792.22 x 333.72 mm	
	Display Surface : Non-Glare	
	Backlight Type : LED	
	Panel Type : VA	
	Viewing Angle (CR≥10, H/V) : 178°/ 178°	
	Curvature : 1500R	
	Pixel Pitch : 0.2318mm	
	Resolution : 3440x1440	
	Color Space (DCI-P3) : 90%	
	Brightness (HDR, Peak) : 400 cd/m ²	
	Brightness (Typ.) : 400cd/m ²	
	Contrast Ratio (Typ.) : 4000:1	
	Display Colors : 16.7M	
	Response Time : 1ms MPRT	
	Refresh Rate (Max) : 180Hz	
	Flicker-free : Yes	
Speaker	Trace Free Technology : Yes	
	GameVisual : Yes	
	Color Temp. Selection : Yes(4 modes)	
	GamePlus : Yes	
	PIP / PBP Technology : Yes	
	HDCP : Yes, 2.2	
	Extreme Low Motion Blur : Yes	
	VRR Technology : Yes (Adaptive-Sync)	
	GameFast Input technology : Yes	
	Shadow Boost : Yes	
I/O Ports	DisplayWidget : Yes, DisplayWidget Center	
	Low Blue Light : Yes	
Signal Input:	Yes(2Wx2)	
	Signal Input: DisplayPort 1.4 x 2 (HBR3) HDMI(v2.0) x 2 USB Hub : 4x USB 3.2 Gen 1 Type-A	
PC Audio Input :	Yes (3.5 mm Mini-jack)	
Signal Frequency	DisplayPort: 290 KHz~290 KHz (H)/ 48~180 Hz (V)	
	HDMI: 30~230K Hz (H) / 48~144 Hz (V)	
Power Consumption	Power Consumption : <18W*	
	Power Saving Mode : <0.5W	
	Power Off Mode : <0.3W	
	Voltage : 100-240V, 50/60Hz	
Mechanical Design	Tilt : Yes (+23° ~ -5°)	
	VESA Wall Mounting : 100x100mm	
Security	Kensington lock	
Dimension (W x H x D)	Phys. Dimension : 80.9 x 44.8 x 21.3 cm (31.85" x 17.64" x 8.39")	
	Phys. Dimension without Stand : 80.9 x 36.6 x 10.7 cm (31.85" x 14.41" x 4.21")	
	Box Dimension : 94.0 x 46.6 x 19.8 cm (37.01" x 18.35" x 7.80")	
Weight	Net Weight : 7.6 kg (16.76 lbs)	
	Net Weight without Stand : 6.4 kg (14.11 lbs)	
	Gross Weight : 10.8 kg (23.81 lbs)	
Accessories	DisplayPort cable, L-shaped Screwdriver, Power cord, Quick start guide, USB Type-B to A cable, Warranty Card	
Certificate	TÜV Flicker-free	
	TÜV Low Blue Light	
	VESA DisplayHDR 400	
	AMD FreeSync FSC MIX	

*1ms MPRT spec is based on internal testes. Response time may vary depending on test conditions

** measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection