


# MegaRAID® SAS 9361-8i

High Performance 12Gb/s PCI Express  
SATA+SAS RAID Controller



LSI MegaRAID SAS 9361-8i

### Key Features

- High performance 12Gb/s data transfer rates
- Eight internal 12Gb/s SATA+SAS ports
- Two mini-SAS SFF8643 internal connectors (horizontal mount)
- LSI SAS3108: 1.2GHz PowerPC® 476 dual core 12Gb/s ROC
- PCI Express 3.0 host interface
- 1GB DDRIII cache memory
- RAID levels 0, 1, 5, 6, 10, 50, and 60
- Support for CacheVault® flash cache protection

### Key Advantages

- 12Gb/s solutions accelerate performance for next-generation datacenters, web and cloud
- Delivers enterprise-class data protection and security
- Preserves investment in 6Gb/s and 3Gb/s drives
- Support for LSI Advanced Software options
- Connect up to 128 3Gb/s, 6Gb/s, or 12Gb/s SATA and SAS devices

### Unmatched RAID Performance for Next-Generation Servers and Storage

The explosive growth of data in cloud and enterprise datacenters is driving the need for a higher performance storage interface to speed the ability of critical applications to access data. LSI first-to-market 12Gb/s SAS solutions are designed to deliver the performance and data protection capabilities required for the most demanding next-generation server and storage platforms. Offering up to double the data transfer rate of 6Gb/s SAS solutions, 12Gb/s SAS allows the SAS infrastructure to deliver bandwidth that can fully utilize that of PCI Express® 3.0 with a single controller card. The MegaRAID SAS 9361-8i, with eight internal ports, delivers two 1.2GHz PowerPC® processor cores and a 72-bit DDRIII interface that drives 1GB cache memory. Powered by the LSI SAS3108 dual-core ROC, the 9361-8i controller includes the latest PCI Express 3.0 and 12Gb/s SAS technology and helps users to support increased scaling of hard disk drives (HDDs) and maximize the performance benefits of solid state drives (SSDs).

### Enterprise Data Protection

Standard support for the most popular RAID levels and accessories, including RAID 5, RAID 6, and CacheVault® Flash cache protection module, further strengthen the data protection capabilities of the MegaRAID SAS 9361-8i. A new enterprise feature employed by the 12Gb/s MegaRAID SAS controllers is advanced drive diagnostic technology. In the event of a physical drive failure, the drive is placed in shield state and the MegaRAID controller starts drive diagnostics to determine if the drive is indeed failed or can be restored. This saves customers time, money and lost compute time associated with transient drive failures and unnecessary drive returns.

### Support for Advanced Software Options

The LSI family of 12Gb/s MegaRAID controllers are designed to support LSI advanced software options that provide system integrators and VARs with enhanced performance and data protection capabilities. These software options help enable end users to address key business challenges while helping to deliver a higher return on their IT investments. MegaRAID CacheCade™ Pro 2.0 software (optional) and MegaRAID Fast Path software (included) boost transactional I/O performance of solid state disk configurations, while SafeStore™ software enables enhanced data protection and security when used with encryption capable devices.

## MegaRAID SAS 9361-8i

Solution Provided	Eight-port internal 12Gb dual core ROC-based SAS solution for data center, cloud, and performance-hungry applications using up to 128 SAS or SATA devices	
Physical Dimensions	MD2 low profile (6.6" X 2.536")	
Connectors	Two mini-SAS SFF8643 internal connectors (horizontal mount)	
Device Support	Up to 128 SAS and/or SATA devices	
Host Bus Type	x8 lane PCI Express 3.0 compliant	
Data Transfer Rates	Up to 12Gb/s per port	
I/O Processor / SAS Controller	LSISAS3108 dual core RAID on Chip (ROC)	
Cache Memory	1GB 1866MHz DDRIII SDRAM	
Cache Protection	Optional CacheVault Flash Module (LSICVM02) – Includes CVFM04, CVPM02, mounting clip, and cable	
Key RAID Data Protection Features	<ul style="list-style-type: none"> <li>• RAID levels 0, 1, 5, and 6</li> <li>• RAID spans 10, 50, and 60</li> <li>• Online Capacity Expansion (OCE)</li> <li>• Online RAID Level Migration (RLM)</li> <li>• Auto resume after loss of system power during array rebuild or reconstruction (RLM)</li> <li>• Single controller Multipathing</li> <li>• Load Balancing</li> <li>• Configurable stripe size up to 1MB</li> <li>• Fast initialization for quick array setup</li> <li>• Check Consistency for background data integrity</li> <li>• SSD Support with SSD Guard™ technology</li> <li>• Patrol read for media scanning and repairing</li> <li>• 64 logical drive support</li> </ul>	<ul style="list-style-type: none"> <li>• Up to 64TB LUN support</li> <li>• DDF compliant Configuration on Disk (COD)</li> <li>• S.M.A.R.T support</li> <li>• Global and dedicated Hot Spare with Revertible Hot Spare support <ul style="list-style-type: none"> <li>– Automatic rebuild</li> <li>– Enclosure affinity</li> <li>– Emergency SATA hot spare for SAS arrays</li> </ul> </li> <li>• Enclosure management – SES (inband) – SGPIO (sideband)</li> <li>• Databolt™ bandwidth optimizer technology support for compatible expander-based enclosures</li> <li>• Shielded state drive diagnostic technology</li> </ul>
Operating Temperature	Maximum ambient: Controller Card: 55°C, with optional CacheVault accessory (LSICVM02): 55°C	
Operating Voltage	+3.3V, +12V	
MTBF (Calculated)	1,343,187 hours	
Hardware Warranty	3 years, free 5x8 phone support, advanced replacement option	
Regulatory Certifications	EN55022, EN55024, EN60950, EN 61000-3-2, EN 61000-3-3; FCC Class A, Class B; UL1950; UL; CSA C22.2; VCCI; RRL for MIC; BSMI; C-tick	
MegaRAID Management Suite	<ul style="list-style-type: none"> <li>• MegaRAID Storage Manager</li> <li>• StorCLI (command-line interface)</li> </ul>	<ul style="list-style-type: none"> <li>• CTRL-R (BIOS configuration utility)</li> <li>• HII (UEFI Human Interface Infrastructure)</li> </ul>
SSD Optimization	<ul style="list-style-type: none"> <li>• MegaRAID CacheCade Pro 2.0 Software leverages SSDs in front of HDD volumes to create high-capacity, high-performance controller cache pools (Optional Upgrade)</li> <li>• MegaRAID Fast Path Software provides high-performance I/O acceleration for SSD arrays connected to 6Gb/s MegaRAID SATA+SAS controllers (Included)</li> </ul>	
Compliances	EMC: Class B-US (CFR 47, P15B); Canada (ICES-003); Japan (V-3/02.04); Europe (EN55022/EN55024); Australia/New Zealand (AS/NZS 3548); Safety: EN60950	
OS Support	Extensive support includes Microsoft® Windows® Server 2012/8 & 7/2008/Vista/2003/XP, Linux®, Solaris™ (x86), Netware®, FreeBSD®, VMware® and more. Visit the LSI download center for the most complete list of supported operating systems: <a href="http://www.lsi.com/channel/support">www.lsi.com/channel/support</a>	

## Ordering Information

## MegaRAID SAS 9361-8i

Kit: LSI00416  
Single: LSI00417

## LSICVM02 CacheVault Kit

LSI00418



For more information and sales office locations, please visit the LSI website at: [www.lsi.com](http://www.lsi.com)

**North American Headquarters**  
San Jose, CA  
T: +1.866.574.5741 (within U.S.)  
T: +1.408.954.3108 (outside U.S.)

**LSI Europe Ltd.  
European Headquarters**  
United Kingdom  
T: [+44] 1344.413200

**LSI KK Headquarters**  
Tokyo, Japan  
T: [+81] 3.5463.7165

LSI, the LSI & Design logo, and the Storage. Networking. Accelerated. tagline are trademarks or registered trademarks of LSI Corporation. All other brand or product names may be trademarks or registered trademarks of their respective companies.

LSI Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI; nor does the purchase, lease, or use of a product or service from LSI convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI or of third parties.

Copyright ©2013 by LSI Corporation. All rights reserved. > 1113