

PATH TO THE FUTURE


Wer beim Gaming der Beste der Besten sein will, braucht nicht nur überlegene Skills, sondern auch eine überragende Ausrüstung, die ihm beim Gefecht mit seinen Widersachern den entscheidenden Vorteil gibt. Der MSI MAG 274PFWDE ermöglicht mit einer blitzschnellen Reaktionszeit von 1ms und einer rasanten Bildwiederholungsrate von 180 Hz absolut schlierenfreie Darstellungen mit butterweichen Bildübergängen für nie dagewesene Bildqualität. Ganz egal ob entspannte Gaming-Session oder hektische Online-Matches: Der 27 Zoller mit FHD-Auflösung verbindet Profi-Gaming von chirurgischer Präzision mit einem nie dagewesenem visuellen Erlebnis und ist damit die erste Wahl für E-Sportler und Grafik-Enthusiasten gleichermaßen. Schneller, präziser, besser – das ist der MAG 274PFWDE von MSI.



Picture and logos

SELLING POINTS

- Rapid IPS-Panel – Bietet eine schnelle Reaktionszeit von 1 ms GtG und optimiert Bildschirmfarben und Helligkeit.
- 180Hz Bildwiederholrate – Schnellere Reaktion durch flüssigere Bilder.
- 1 ms GtG Reaktionszeit – Verhindert Bildschirmrisse und ungleichmäßige Bildraten.
- Verstellbarer Standfuß – Ermöglicht einfache Anpassung der Monitorposition für maximale Ergonomie.
- Adaptive-Sync-Technologie – Flüssiges, ruckelfreies Gaming ohne Tearing.
- HDR Ready – Bietet beeindruckende Details durch Anpassung von Kontrast und Schatten.
- AI Vision – Die neue AI Vision-Technologie kann nicht nur Details in dunklen Bereichen sichtbar machen, sondern auch die Gesamthelligkeit erhöhen und Farben satter darstellen.



1. 5-Wege Joystick Navigation
2. HDMI™ 2.1 (FHD@180Hz)
3. Display Port 1.2a
4. Kopfhörerausgang
5. Stromanschluss
6. Kensington Lock



MONITOR

MAG 274PFWDE

MAG 274PFWDE

SPECIFICATION

Model	SKU Number	9S6-3CC29H-299
	Entity MKT Name	MAG 274PFWDE
	Part No	9S6-3CC29H-299
	Color	ID1/White-White
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~200 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	103%/86%
	NTSC (CIE1931 area percentage/overlap)	89%/82%
	sRGB (CIE1976 area percentage/overlap)	117%/99%
	sRGB (CIE1931 area percentage/overlap)	126%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	100%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/86%
	DCI-P3 (CIE1976 area percentage/overlap)	93%/92%
	DCI-P3 (CIE1931 area percentage/overlap)	92%/92%
	Rec.709 (CIE1976 area percentage/overlap)	117%/99%
	Rec.709 (CIE1931 area percentage/overlap)	126%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	External Adaptor 12V 3A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



M O N I T O R

MAG 274PFWDE

M A G 2 7 4 P F W D E

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	75x75mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 196.5 x 402.1
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 69.8 x 362.5
	Stand Dimension (WxDxH) (mm)	242.2 x 196.5 x 399.2
	Weight (Net kg)	6.05
	Weight Without Stand (kg)	3.95
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	81.5 x 14.5 x 50.2
	Outer Carton Dimension (WxDxH) (cm)	83 x 15.8 x 52.6
	Weight (Gross kg)	7.85
Barcode Info	EAN	4711377196475